

## Vise Mount Ferrule Crimper Cat. No. VMCC150

Vise Operated  
Top Entry Wire Cavities  
Crimps Insulated and Uninsulated Ferrules

<b>Crimping Range</b>	2/0; 3/0; 4/0; 250 MCM (70; 95; 120; 150 mm <sup>2</sup> )
<b>Weight</b>	5.06 lbs.
Spring Loaded for Self Opening, Trapezoidal Crimp Geometry, Hardened Steel	


## Hand-Operated Ferrule Crimpers

Conta-Clip Hand-Operated Ferrule Crimpers are used to mechanically crimp insulated and uninsulated ferrules onto wires and cables. They are manufactured to exacting specifications, ensuring the best possible connection between the ferrule and conductor.


Choose from front or side wire entry crimpers with one or individual crimp cavities.

- Positive Ratcheting with Emergency Release
- Provide Maximum Crimp Force with Reasonable Hand Pressure
- Designed to Reduce Hand Stress
- Features Hardened Dies and Steel Frames (PZU4 plastic frame)

**Standard Pack is 1 for all Ferrule Crimpers**



Front Wire Entry



Side Wire Entry

**PZU 4**  
Front/Side Wire Entry




**Single Crimp Cavity**  
Cat. No: 1464.0  
AWG Wire Size: 20-12  
mm<sup>2</sup> Ferrule Size: .5-4.0

**PZU S**  
Side Wire Entry



**Multiple Crimp Cavities**  
Cat. No: 3055.0  
AWG Wire Size: 26-10  
mm<sup>2</sup> Ferrule Size: .14-6.0

**PZU 6**  
Front Wire Entry



**Single Crimp Cavity**  
Cat. No: 1100.0  
AWG Wire Size: 26-10  
mm<sup>2</sup> Ferrule Size: .14-6.0

**PZU 16**  
Front Wire Entry



**Single Crimp Cavity**  
Cat. No: 1465.0  
AWG Wire Size: 8-6  
mm<sup>2</sup> Ferrule Size: 10.0-16.0

**PZU 25**  
Side Wire Entry



**Multiple Crimp Cavities**  
Cat. No: 3057.0  
AWG Wire Size: 8,6,4  
mm<sup>2</sup> Ferrule Size: 10, 16, 25

**PZU 35**  
Side Wire Entry



**Multiple Crimp Cavities**  
Cat. No: 1466.0  
AWG Wire Size: 4,2  
mm<sup>2</sup> Ferrule Size: 25, 35

**PZU 50**  
Side Wire Entry



**Single Crimp Cavity**  
Cat. No: 1467.0  
AWG Wire Size: 1/0  
mm<sup>2</sup> Ferrule Size: 50

**PZU 16/E**  
Side Wire Entry



**Multiple Crimp Cavities**  
Cat. No: 3056.0  
AWG Wire Size: 20-6  
mm<sup>2</sup> Ferrule Size: 0.5-16.0

