

Pneumatic Handheld and

Conta-Clip's Pneumatic Ferrule Crimpers are used to mechanically crimp insulated and uninsulated ferrules onto wires and cables. When crimping volume is high, they provide a cost effective alternative to hand crimping while eliminating the possibility of carpal tunnel syndrome.

Conta-Clip's Pneumatic Crimpers are supplied fully assembled and ready for immediate hookup to a compressed air supply and use. Just install a ferrule over a stripped wire and insert it into the appropriate crimp cavity opening. To start the crimping cycle, press the actuating lever on the handheld unit or the footswitch pedal on the tabletop unit. Upon release of the actuating lever or the footswitch pedal, the crimping cycle is completed automatically opening the tool and allowing for removal of the crimped ferrule.

All Pneumatic Crimpers produce a trapezoidal crimp cross section ensuring an optimum mechanical and electrical connection between the ferrule and the conductor.



Pneumatic Handheld Crimper IAC25

Cat. No. IAC25

Single Front and Side Wire Entry Crimp Cavity
Crimps Insulated and Uninsulated Single and Dual Ferrules

Crimping Range Single Ferrules	24-14 AWG (0.25 - 2.5 mm ²)
Crimping Range Dual Ferrules	2x24-2x16 AWG (2x0.5-2x1.5 mm ²)
Operating Air Pressure	60-90 PSI (4-6 bar)
Weight	0.95 lbs.
1/4" Female Air Hose Connector Included	

Pneumatic Handheld Crimper IAC100

Cat. No. IAC100

Multiple Side Wire Entry Crimp Cavities
Crimps Insulated and Uninsulated Single Ferrules

Crimping Range Single Ferrules	12-8 AWG (4-10 mm ²)
Operating Air Pressure	60-90 PSI (4-6 bar)
Weight	0.95 lbs.
1/4" Female Air Hose Connector Included	

Tabletop Ferrule Crimpers



Pneumatic Tabletop Crimper IAC25T Cat. No. IAC25T

Foot Switch Operated
Single Front and Side Wire Entry Crimp Cavity
Crimps Insulated and Uninsulated Single and Dual Ferrules

Crimping Range Single Ferrules	24-14 AWG (0.25-2.5 mm ²)
Crimping Range Dual Ferrules	2x24-2x16 AWG (2x0.5-2x1.5 mm ²)
Operating Air Pressure	60-90 PSI (4-6 bar)
Weight	2.20 lbs.
1/4" Female Air Hose Connector and Table Clamp Included	



Balancer Cat. No. BCC01

Can be used with
Handheld Crimper



Pneumatic Tabletop Crimper IAC100T Cat. No. IAC100T

Foot Switch Operated
Multiple Side Wire Entry Cavities
Crimps Insulated and Uninsulated Single Ferrules

Crimping Range Single Ferrules	12-8 AWG (4-10 mm ²)
Operating Air Pressure	60-90 PSI (4-6 bar)
Weight	2.20 lbs.
1/4" Female Air Hose Connector and Table Clamp Included	



Magnetic Holder Cat. No. MHCC10

Can be used with
Handheld Crimper